

CARACTERISTIQUES :

- Jetables
- Non poudré
- Couleur latex naturel : blanc laiteux
- 100% caoutchouc naturel
- Facile à mettre - facile à enlever
- Contrôle de qualité continue

Epaisseur : +/- 0.11mm

Poids : 7.6 gr +/- 0.3gr

Emballage : boîte de 100 pièces



EN ISO 374-5:2016



Marking of gloves protecting against bacteria and fungi

EN ISO 374-5:2016	Level
Protection against bacteria and fungi	Pass
Protection against viruses	Pass

ISO 374-1:2016/Type B	Tested in accordance with ISO 374-1:2016		
	Chemicals	EN ISO 374-1:2016 Penetration Level	EN374-4:2013 Degradation
	B = Acetone	0	58.1%
	K = 40% Sodium Hydroxide	6	11.5%
	O = 25% Ammonium Hydroxide	0	-94.4%
	S = 40% Hydrofluoric Acid	3	X
	T = 37% Formaldehyde	6	-25.0%

Level	1	2	3	4	5	6
Minimum Breakthrough times, min	>10	>30	>60	>120	>240	>480

Note: The gloves fulfill the requirements of EN ISO 374-1:2016. The gloves are designed to protect against chemical risk in accordance with EN ISO 374:2016 and have met the general requirements in accordance with EN 420:2003+A1:2019. The penetration resistance has been assessed under laboratory conditions and related only to the tested specimen.

Note: The above mentioned protection performance of the gloves may vary under different working condition or the protection performance of the gloves is based on laboratory test condition hence may vary from the actual working conditions.



Latex gloves for single use. Inspect gloves for damage before use. Mechanical hazards: gloves only protect against dirt. Used gloves have to be disposed of according to local regulations.

This product is manufactured from a 100% latex compound.

STORAGE RECOMMENDATIONS:

Do not store latex gloves where temperature could rise above 104°F / 40°C. Store in a cool dry place. Keep opened boxes out of direct sunlight. Keep out of humid places.

EN

Examination and protective gloves, latex powder-free, disposable, non-sterile, personal protective equipment cat. I against minimal risks, below 270mm-length for special purpose, ambidextrous, store in a cool, dry place at 5-30°C protect from sunlight, fluorescent and ozone, dispose of after use in accordance with the applicable regulations, product quality is not guaranteed if the packaging is damaged. Manufactured in accordance with EEC directives 93/42 MVD Class-1; PPE Regulation (EU) 2016/425 Category-1, meet the requirements of EN 455,

LOT 2007315

07-2025

07-2020

Taille XL - réf. IN26578